

HS-1 B and HS-1 P Headset Microphone

Whether you're presenting for television or live on-stage; in a 20,000 seat auditorium or in a house of worship, RØDE has all your audio requirements covered with the reliable and intuitive HS1 headset.

Featuring the pure, clear audio and low handling noise that RØDE is celebrated for, the HS1 is built to deliver and to last.

Subtle, ergonomic design including three axes of mechanical adjustment, a malleable, ultra lightweight tube arm and headband, and the choice of either black (HS1-B) or pink (HS1-P) models ensure the perfect fit and function for each individual.

Knowing that versatility is paramount in any product, RØDE has developed the MiCon™ connector system which provides seamless integration between all of RØDE's compact wearable microphones and a wide range of wireless systems.

Visit the MiCon™ product page for a full list of available adaptors and the supported devices.



RØDE has always offered industry leading warranty and after sales service on its products, and the HS1 is no exception, offering an innovative five year warranty that gives you total piece of mind for five years after purchase.

Specifications:

Power	Min 2V - Max 5V through MiCon wireless adaptors P48 through MiCon XLR adaptor
Acoustic Principle	Permanently polarised condenser
Directional Pattern	Omni-directional
Frequency range	60Hz - 18kHz
Output impedance	3kΩ Typical
Signal noise ratio	69dB
Equivalent noise	25dBA SPL (per IEC651)
Maximum SPL	110dB (clipping SPL)
Maximum output voltage	189mV (Calc. from max SPL peak before clip)
Sensitivity	-33.5dB re 1 V/Pa (1.6mV @ 94dB SPL) ± 3dB @ 1kHz
Weight	6.5gm
Dimensions	65mmH x 140mmW x 200mmD

